



Technical datasheet No.: **1380.4**

Product: VALMEX® nautica heavy, leather embossing

Article No.: 4240 6241

| | | | |
|-----------------------------------|---|--------------------|-------------|
| Type of coating and finish | | | |
| Type of coating | PVC one side | | |
| Finish | one side lacquered, textured surface, fungicide, leather embossing (outside) | | |
| Total weight | 445 g/m ² | EN ISO 2286-2 | |
| Tensile strength warp/weft | 2500 / 2500 N/50 mm | DIN EN ISO 1421/V1 | |
| Tear strength warp/weft | 300 / 300 N | DIN 53363 | |
| Cold resistance | -25 °C | DIN 53361 | |
| High Temperature | +70 °C | LB 3.15 | |
| Light fastness | 7-8 Note, Value | DIN EN ISO 105 B02 | |
| Weather fastness | 7-8 Note, Value | DIN EN ISO 105 B04 | |
| Crack resistance (z) | no cracks | @ 100000 x | DIN 53359 A |
| Base fabric | | | |
| Material | PES | DIN ISO 2076 | |
| Yarn count | 1100 dtex | DIN ISO 2060 | |
| Weave | L 1/1 | | |
| for base fabric | low-wick | | |

These indicated technical data are based on average results. Due to production procedures slight deviations can occur. All technical data are in accordance with the present standard of knowledge and give product information without legal binding. All data apply to new products. Applications suggested do not release the customer to test material for its intended application.